



Safety Data Sheet

Product: Crafted Hardwood

Document Version: 1.0

Date: 19 August 2023

Table of Contents

| | |
|--|---|
| 1. Identification..... | 3 |
| 2. Hazard(s) Identification..... | 3 |
| 3. Composition and information on ingredients..... | 3 |
| 4. First Aid Measures..... | 3 |
| 5. First Aid Treatment:..... | 4 |
| 6. Firefighting Measures..... | 4 |
| 7. Accidental Release Measures..... | 4 |
| 8. Handling and Storage Information..... | 4 |
| 9. Exposure Controls and Personal Protection..... | 4 |
| 10. Physical and Chemical Properties..... | 5 |
| 11. Stability and Reactivity..... | 6 |
| 12. Toxicological Information..... | 6 |
| 13. Ecological Information..... | 7 |
| 14. Disposal Considerations..... | 7 |
| 15. Transport information..... | 7 |
| 16. Regulatory information..... | 7 |
| 17. Any other relevant information..... | 7 |

1. Identification

- **Products:** This SDS applies to all “Crafted Hardwood” products from Crafted Hardwoods.
- **Supplier:** Crafted Hardwoods Pty Ltd
PO Box 44
Campbell ACT 2612
Phone: 1300 320 610
Email: info@craftedhardwoods.com
- **Emergency Phone Number:** 13 11 26, Australian Poisons Information Centre
- **Use:** General timber usage, furniture, and fitments.

2. Hazard(s) Identification

- **Hazardous Statement:** Not classified as hazardous according to Work Safe Australia Regulations.
- **Label Elements:** No signal word, pictograms, hazard, or precautionary statements have been allocated.

3. Composition and information on ingredients

These products are a mixture of wood veneers (various species available) and a thermo-set resin.

| Item | GHS Hazard Class | GHS Hazard Category | Proportion by weight |
|--------------------------------|------------------|---------------------|----------------------|
| Wood veneer | None | None | > 90% |
| Other non-hazardous components | None | None | < 10% |

4. First Aid Measures

Exposure to wood dust produced during machining may result in the following acute health effects: Handling wood may cause splinters.

- **Ingestion:** Very unlikely to occur but may result in abdominal discomfort.
- **Eye:** May be irritating to the eyes causing redness and discomfort.
- **Skin contact:** May result in irritation.
- **Inhaled:** May be irritating to the nose, throat, and lungs.

- **Chronic Health Effects:** Repeated inhalation of dust from this product may increase the risk of nasal cavity cancer. Exposure to wood dust in some susceptible people may result in respiratory and skin sensitivity leading to asthma and dermatitis respectively. However, if the work practices noted in this SDS are followed, and exposure to airborne dusts are kept low, no acute or chronic health effects are anticipated.

5. First Aid Treatment:

- **Ingestion:** If swallowed, give water to drink. Seek medical attention if any abdominal discomfort.
- **Eyes:** Flush thoroughly with water for at least 15 minutes. Remove contact lenses before flushing. If irritation persists, seek medical attention.
- **Skin:** Wash thoroughly with mild soap and water. Remove contaminated clothing.
- **Inhaled:** Leave the dusty area.
- **Advice to doctor:** Treat symptomatically.

6. Firefighting Measures

Burning or smouldering boards or wood dust can generate carbon dioxide and other pyrolysis products typical of burning organic material. Dry wood dust in high concentrations can be explosive. Use water or dry chemical powder fire extinguishers.

7. Accidental Release Measures

Small quantities of wood dust should be cleaned up by vacuuming or wet sweeping.

For release of large quantities of dust: evacuate the area immediately. Isolate the hazard area. Keep out unnecessary and unprotected personnel. Use the personal protective equipment recommended in Section 8. Although no specific Environmental Precautions required for wood dusts: it is good practice to prevent releases into the environment. If a large quantity of dust is inside a building, prevent it from entering drains, ventilation systems and confined areas.

8. Handling and Storage Information

Crafted Hardwood Products should be stored in a well-ventilated area away from sources of heat, flame, or sparks.

Not classified as dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road, Rail, Sea, and Air.

No special transport requirements are considered necessary.

9. Exposure Controls and Personal Protection

Safety Data Sheet

The Worksafe Australia Exposure Standards for wood dust, published 27 April 2018 are:

| Item | TWA (mg/m ³) | STEL (mg/m ³) | Other information |
|---------------|--------------------------|---------------------------|---|
| Softwood Dust | 5 | 10 | Sensitive to skin and respiratory tract |
| Hardwood Dust | 1 | - | Sensitive to skin and respiratory tract |

TWA – Time Weighted Average

STEL – Short Term Exposure Limit

Keep exposure as low as practicable with the aim of maintaining inspirable wood dust levels below 1.0 mg / m³ TWA.

- **Engineering Controls:** All work with Crafted Hardwood Products must be carried out in such a way as to minimise exposure to wood dust. Under factory conditions, the use and processing of Crafted Hardwood Products should be done with equipment fitted with local exhaust ventilation devices capable of removing dust at source. Measures should be taken to eliminate the build-up of static electricity.
- **Skin Protection:** Wear industrial gloves (AS2161), loose comfortable clothing, and boots. Long-sleeved shirts and long trousers are recommended if skin irritation occurs. Wash with mild soap and water after working with Crafted Hardwood Products. Launder work clothes regularly and separately from other clothes.
- **Respiratory Protection:** If wood dust exposures are not sufficiently controlled when machining (sawing, routing, planing, drilling, sanding, etc.) a class P1 or P2 replaceable filter or disposable face piece respirator should be worn. Respirators should be selected, used, and maintained in accordance with AS/NZS 1715/1716.
- **Eye Protection:** Safety glasses or non-fogging goggles to meet (AS/NZS 1337) should be worn when machining.

10. Physical and Chemical Properties

- **Appearance:** Wood, colour is specific to species used.
- **Physical State:** Solid
- **Flammability:** Fine airborne dust, generated when the product is machined, can ignite spontaneously.
- **Auto ignition temp:** >200oC
- **Odour:** Not determined.
- **Odour Threshold:** Not determined.
- **Solubility in water:** Highly insoluble

11. Stability and Reactivity

- **Reactivity:** Not reactive under normal conditions of use. Wood dust is reactive with oxidizing materials. Combustible in the presence of the following materials or conditions: open flames, sparks, and static discharge.
- **Chemical stability:** Stable under normal conditions of storage and use.
- **Possibility of hazardous reactions:** None expected under normal conditions of storage and use.
- **Conditions to avoid:** Generation of dust through cutting, sanding, or disturbing the pure product. Open flames, sparks, static discharge, heat, and other ignition sources.
- **Incompatible materials:** Wood dust is incompatible with oxidizing materials.
- **Hazardous decomposition products:** Under normal conditions of storage and use, hazardous decomposition products should not be produced.

12. Toxicological Information

- **Acute toxicity:** No information available.
- **Skin corrosion/irritation:** Handling and / or processing this material may generate a dust which can cause irritation of the skin. Potential symptoms include dermatitis.
- **Serious eye damage/irritation:** Handling and / or processing this material may generate a dust which can cause irritation of the eyes.
- **Respiratory or skin sensitisation:** Wood dust may be a dermal and respiratory sensitizer.
- **Germ cell mutagenicity:** No information available.
- **Carcinogenicity:** Not classified as a carcinogen. However, repeated exposure to wood dust may result in result in nasal and paranasal sinus cancers (IARC Group 1). Adverse health effects are usually associated with long-term exposure to high dust levels.
- **Reproductive toxicity:** No information available.
- **Specific Target Organ Toxicity (STOT)—single exposure:** Handling and / or processing this material may generate a dust which can cause respiratory tract irritation, asthma, coughing / wheezing, and sinusitis.
- **Specific Target Organ Toxicity (STOT)—repeated exposure:** Repeated inhalation of dust can produce varying degrees of respiratory irritation or lung damage. Chronic exposure to wood dusts can result in dermatitis reactions, asthma, pneumonitis, and coughing, wheezing, fever and other signs and symptoms associated with chronic bronchitis.
- **Aspiration hazard:** No information available.

13. Ecological Information

- **Toxicity:** No information available.
- **Persistence and degradability:** No information available.
- **Bio accumulative potential:** No information available.
- **Mobility in soil:** No information available.
- **Other adverse effects:** No information available.

14. Disposal Considerations

Offcuts and general waste should be disposed of in accordance with local disposal authority guidelines.

15. Transport information

- **UN Number:** None allocated.
- **Proper Shipping Name:** None allocated.
- **Transport Hazard Class:** None allocated.
- **Packing Group Number:** None allocated
- **IMDG Code:** None allocated.
- **Special Precautions for user:** None available
- **HAZCHEM Code:** None allocated.

16. Regulatory information

End users should consult local publications regarding control of wood dust hazards in the workplace within their state or territory.

17. Any other relevant information

Date of Preparation: 19 August 2023

"Whilst the information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purpose and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, no responsibility can be accepted by us for any loss or damage caused by any person acting or refraining from action"

Safety Data Sheet



as a result of this information".